



# KE61.2

Name: **Clampo Pro terminal**  
1-pole, blue, Al 6-50 mm<sup>2</sup>, Cu 2.5-50 mm<sup>2</sup>

Type: KE61.2

GTIN: 6418677191831

Description: Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm<sup>2</sup>.

Package: 3/30

Unit: PCS



## Technical specification

### Electrical values

Nominal insulation voltage 800 V  
Pollution degree 3  
Nominal current Cu 160 A, Al 145 A

### Ratings

ETIM class Feed-through terminal block

### Mechanical

Tightening torque 4 Nm (2.5-4mm<sup>2</sup>), 12 Nm (6-50mm<sup>2</sup>)

### Dimensions

Weight 0.03 kg  
Conductor cross-section Cu 2,5-50 Al 6-50

### Temperatures

Operating temperature ≤ 80 °C

### Features

Mounting DIN rail  
Number of poles 1  
Screw head Hexagon  
Screw head size 5 mm

### Materials

Housing Polyamide

### Colors

Color Blue

### US specific

Conductor size 1/0-6  
Maximum voltage 600 V  
Tightening torque 90 Lb-In



Saves Your Energy

## PRODUCT CARD

2.1.2016

2/2

# KE61.2

Max. current

Cu 150A, Al 120A

**Certificates**

Connector class

A

Standards

EN 60947-7-1, EN 61238-1, UL 1059

UL category

XCFR2

UL File no.

E192532, E192532

---

Ensto Finland Oy

Ensio Miettisen katu 2  
P.O.Box 77  
06101 Porvoo, Finland

Tel. +358 204 76 21  
Fax +358 204 76 2516

[www.ensto.com](http://www.ensto.com)